

Monitor up to 12 environmental parameters with one tiny instrument.

Light weight, tiny size with simple, one-hand, operation. All units read air speed in addition to the wide selection of environmental parameters listed below. Will sense airflow as low as 0.4 m/s. Replaceable snap-in anemometer vane. All models feature min/max, hold, a backlight and come complete with a wrist strap, carry pouch, and button cell battery. Model 850027 accurately measures liquid and solid temperatures using the optional Pt 1000 penetration probe.

No.	Description
850025	Mini Environmental Quality Meter
850026	Mini Environmental Quality Meter
850027	Mini Environmental Quality Meter
850025V	Replacement Vane
850027P	Pt 1000 Temperature Probe

DIM: 4¾" x 1¾" x 7/8" (120 x 45 x 22.25 mm)
WEIGHT: 5.6 oz (160 g)

	Range	Resolution	Accuracy	850025	850026	850027
Wind Speed	80 ~ 3937 ft/min 0.4 ~ 20.0 m/s 1.4 ~ 72.0 km/h 0.9 ~ 44.7 mile/h 0.8 ~ 38.8 knots 32 ~ 122 °F (0 ~ 50 °C)	1 ft/min 0.1 m/s 0.1 km/h 0.1 MPH 0.1 knots 0.1 °F/°C	≤ 20 m/s: ± 3% F.S. > 20 m/s: ± 4% F.S.	✓	✓	✓
Air Temperature	32 ~ 122 °F 0 ~ 50 °C	0.1 °F 0.1 °C	± 2.5 °F ± 1.2 °C	✓	✓	✓
RH	10 ~ 95 %RH	0.1 %RH	< 70% RH: ± 4% RH ≥ 70% RH: ± (4% rdg +1.2% RH)	✓	✓	✓
Air Volume	0.024 ~ 36000 CMM 0.847 ~ 1271300 CFM	0.001/0.01/0.1/1 0.001/0.01/0.1/1 /10 (x10)/100 (x100)			✓	✓
Wind Chill	15.0 ~ 112.0 °F -0.4 ~ 44.2 °C	0.1 °F 0.1 °C	± 3.6 °F ± 2.0 °C		✓	✓
Heat Stress Index	32 ~ 212 °F 0 ~ 100 °C	0.1 °F 0.1 °C	± 3.6 °F ± 2.0 °C		✓	✓
Dew Point	-13.5 ~ 120.0 °F -25.3 ~ 49.0 °C	0.1 °F 0.1 °C	Calculate from the humidity/temperature value		✓	✓
Wet Bulb	22.2 ~ 120 °F -5.4 ~ 49.0 °C	0.1 °F 0.1 °C	Calculate from the humidity/temperature value		✓	✓
PT 1000 ohm Probe (optional)	14.0 ~ 212.0 °F -10.0 ~ 100.0 °C	0.1 °F 0.1 °C	± 2.5 °F ± 1.2 °C			✓
Barometric Pressure	10.0 ~ 999.9 hPa 1000 ~ 1100 hPa 7.5 ~ 825.0 mmHg 0.29 ~ 32.84 inHg	0.1 hPa 1 hPa 0.1 mmHg 0.01 inHg	± 1.5 hPa ± 2 hPa ± 1.2 mmHg ± 0.05 inHg			✓
Altitude	-6000 ~ 30000 ft -2000 ~ 90000 m	1 ft 1 m	± 50 ft ± 15 m			✓
Visible Light	0 ~ 2200 Lux 1800 ~ 20000 Lux 0 ~ 204.0 Fc 170 ~ 1860 Fc	1 Lux 10 Lux 0.1 Ft-cd 1 Ft-cd	± 5% rdg ± 8 dgt			✓

