

ORP Electrode and Conductivity Cell



PO50 GO51 ID4411 ID4521



CD60B CD60TB CD60D4 CD61B1 CD61B01 CD62B ID4522T

Model	PO-50	GO-51	ID-4411	ID-4521
Description	Plastic electrode	Glass electrode	on-line	on-line
Range	±1500 mV	±1500 mV	±1500 mV	±1500 mV
Temp.	0-80°C	0-90°C	0-90°C	0-80°C
Type Ref.	Ag/AgCl	Ag/AgCl	Ag/AgCl	Ag/AgCl
Junction	Fiber	Ceramic	Ground glass sleeve	Cricoid Teflon
Refillable	No	Yes	Yes	No
Body	PC	Glass	Glass	GFRPP
Connector	BNC	BNC	Spade Lug or BNC	Spade Lug or BNC
Size(mm)	160 x 12	160 x 12	160 x 12	176 x 16
Cable	1 m	1 m	1.2 m	5 m

Model	CD-60B	CD-60TB	CD-60D4	CD-61B1	CD-61B01	CD-62B	ID-4522T
Description	Glass cell	Glass cell with temp.	Glass cell	Stainless steel 304	Plastic Cell	on-line	
K value	K=1.0	K=1.0	K=1.0	K=1.0	K=0.1	K=1.0	K=1.0
Sensor	Pt Plate	Pt Plate	Pt Plate	Stainless steel 304	Silver	Pt Plate	
Temp. sensor	N/A	30 K	N/A	N/A	N/A	30 K	
Body	Glass	Glass	Glass	Stainless steel 304	PC	GFRPP	
Connector	BNC	BNC + 3.5 ψ Plug	mini DIN 4 pin	BNC	BNC	BNC	Spade Lug
Size(mm)	155 x 12	155 x 12	155 x 12	160 x 13	160 x 13	160 x 12	176 x 31
Cable	1 m	1 m	1 m	1 m	1 m	1 m	5 m

